

DuraGard® Waterproof Connections

30 Amp Standard Service



Male Plug



Female Connector

Device Ratings and Polarizations

Maximum 600VAC or 250VDC

POLE	WIRE	SAFETY POLARIZATION (RECEPTACLE)	VOLTAGE	CAT. NO. ☐	CAT. NO. ☐
2	3		125VAC	9P33U1	9C33U1
			250VAC	9P33U2	9C33U2
			277VAC	9P33U3	9C33U3
			480VAC	9P33U4	9C33U4
			600VAC	9P33U5	9C33U5
			through 600VAC/250VDC	9P33U0	9C33U0
3	4		125/250VAC	9P34U1	9C34U1
			3Ø 250VAC	9P34U2	9C34U2
			3Ø 480VAC	9P34U4	9C34U4
			3Ø 600VAC	9P34U5	9C34U5
			through 600VAC/250VDC	9P34U0	9C34U0

☐ Add suffix — / xxxx for bushing I.D. (page 65) or conduit adapter assembled.

◆ “W” suffix indicates watertight receptacle;
“F” suffix indicates splash-proof spring flap cover included.

* Consult Technical Services.

DuraGard® Waterproof Connections

30 Amp Reverse Service



Female Receptacle



Female Plug



Male Receptacle

STANDARD BUSHING I.D.: PLUG/CONN.*	CAT. NO. ♦	CAT. NO. □	CAT. NO. ♦
Standard .700"; for optional size, see page 65	9R33U1W	9F33U1	9B33U1F
	9R33U2W	9F33U2	9B33U2F
	9R33U3W	9F33U3	9B33U3F
	9R33U4W	9F33U4	9B33U4F
	9R33U5W	9F33U5	9B33U5F
	9R33U0W	9F33U0	9B33U0F
Standard .750"; for optional size, see page 65	9R34U1W	9F34U1	9B34U1F
	9R34U2W	9F34U2	9B34U2F
	9R34U4W	9F34U4	9B34U4F
	9R34U5W	9F34U5	9B34U5F
	9R34U0W	9F34U0	9B34U0F

□ Add suffix — / xxxx for bushing I.D. (**page 65**) or conduit adapter assembled.

♦ "W" suffix indicates watertight receptacle;
"F" suffix indicates splash-proof spring flap cover included.

* Consult Technical Services.