



Main

| | |
|-----------------------|-----------------------------|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 20 A |
| Voltage Rating | 120/240 V AC 120 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 2P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Pressure plate |
| Options | Shunt trip 120/208/240 V AC |

Complementary

| | |
|------------------------|--|
| Interrupt Rating | 10 KA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz |
| Number of Panel Spaces | 3 |
| Wire Size | AWG 14...AWG 8 copper or aluminium |
| Tightening Torque | 35.40 lbf.in (4 N.m) |
| Height | 2.99 in (76 mm) |
| Width | 2.24 in (57 mm) |
| Depth | 2.91 in (74 mm) |
| Net Weight | 0.90 lb(US) (0.408 kg) |

Environment

| | |
|----------------|----------------------|
| Certifications | UL Listed[RETURN]CSA |
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 00004-QO,QOT 10-30A 1P;10-60A 2P |
| Discount Schedule | DE2A |
| GTIN | 785901493938 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.20 in (8.128 cm) |
| Package 1 Width | 3.60 in (9.144 cm) |
| Package 1 Length | 4.60 in (11.684 cm) |
| Package 1 Weight | 14.40 oz (408.233 g) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|