



Figure similar

MLFB-Ordering data

6SL3220-1YE52-0CP0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data			General tech. specifications	
Input				
Number of phases	3 AC		Power factor λ	0.90 ... 0.95
Line voltage	380 ... 480 V	+10 % -20 %	Offset factor $\cos \varphi$	0.99
Line frequency	47 ... 63 Hz		Efficiency η	0.98
Rated voltage	400V IEC	480V NEC	Sound pressure level (1m)	74 dB
Rated current (LO)	365.00 A	356.00 A	Power loss	4.620 kW
Rated current (HO)	330.00 A	327.00 A	Filter class (integrated)	RFI suppression filter for Category C3
Output			EMC category (with accessories)	Category C3
Number of phases	3 AC		Ambient conditions	
Rated voltage	400V IEC	480V NEC	Standard board coating type	Class 3C2, according to IEC 60721-3-3: 2002
Rated power (LO)	200.00 kW	300.00 hp	Cooling	Air cooling using an integrated fan
Rated power (HO)	160.00 kW	250.00 hp	Cooling air requirement	0.210 m ³ /s (7.416 ft ³ /s)
Rated current (LO)	370.00 A	361.00 A	Installation altitude	1000 m (3280.84 ft)
Rated current (HO)	302.00 A	302.00 A	Ambient temperature	
Rated current (IN)	379.00 A		Operation	-20 ... 45 °C (-4 ... 113 °F)
Max. output current	500.00 A		Transport	-40 ... 70 °C (-40 ... 158 °F)
Pulse frequency	2 kHz		Storage	-25 ... 55 °C (-13 ... 131 °F)
Output frequency for vector control	0 ... 200 Hz		Relative humidity	
Output frequency for V/f control	0 ... 550 Hz		Max. operation	95 % At 40 °C (104 °F), condensation and icing not permissible

Overload capability

Low Overload (LO)

110% base load current IL for 60 s in a 300 s cycle time

High Overload (HO)

150% x base load current IH for 60 s within a 600 s cycle time



MLFB-Ordering data

6SL3220-1YE52-0CP0

Figure similar

Mechanical data		Closed-loop control techniques	
Degree of protection	IP20 / UL open type	V/f linear / square-law / parameterizable	Yes
Size	FSG	V/f with flux current control (FCC)	Yes
Net weight	113 kg (249.12 lb)	V/f ECO linear / square-law	Yes
Width	305 mm (12.01 in)	Sensorless vector control	Yes
Height	999 mm (39.33 in)	Vector control, with sensor	No
Depth	369 mm (14.53 in)	Encoderless torque control	Yes
Inputs / outputs		Communication	
Standard digital inputs		Communication	PROFIBUS DP
Number	6	Connections	
Switching level: 0 → 1	11 V	Signal cable	
Switching level: 1 → 0	5 V	Conductor cross-section	0.15 ... 1.50 mm ² (AWG 24 ... AWG 16)
Max. inrush current	15 mA	Line side	
Fail-safe digital inputs		Version	M10 screw
Number	1	Conductor cross-section	35.00 ... 185.00 mm ² (AWG 1 ... MCM 2 x 350)
Digital outputs		Motor end	
Number as relay changeover contact	2	Version	M10 screw
Output (resistive load)	DC 30 V, 5.0 A	Conductor cross-section	35.00 ... 185.00 mm ² (AWG 1 ... MCM 2 x 350)
Number as transistor	0	DC link (for braking resistor)	
Analog / digital inputs		PE connection	M10 screw
Number	2 (Differential input)	Max. motor cable length	
Resolution	10 bit	Shielded	200 m (656.17 ft)
Switching threshold as digital input			
0 → 1	4 V		
1 → 0	1.6 V		
Analog outputs			
Number	1 (Non-isolated output)		
PTC/ KTY interface			
1 motor temperature sensor input, sensors that can be connected: PTC, KTY and Thermo-Click, accuracy ±5 °C			



Figure similar

MLFB-Ordering data

6SL3220-1YE52-0CP0

Converter losses to EN 50598-2*		Standards
Efficiency class	IE2	Compliance with standards UL, cUL, CE, C-Tick (RCM), EAC, KCC, SEMI F47, REACH

Comparison with the reference converter (90% / 100%)

-43.90 %

CE marking
EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC

Current (I)	Losses (W)	Losses (%)
100%	2936.3 W	1.15 %
50%	1474.5 W	0.58 %
25%	993.7 W	0.39 %
90%	4612.8 W	1.80 %
50%	3548.6 W	1.38 %
50%	1691.5 W	0.66 %
50%	1082 W	0.42 %
25%	2022.4 W	0.79 %

The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values