

# Product data sheet

## Characteristics

### HEPD25C

Surge protection device, HEPD, 25kA, 120/240 V, 1 phase, 3 wire, SPD type 2, consumer pack



#### Main

Product or Component Type	Surge protection device
Range of Product	Square D
Device short name	HEPD
Type of Packing	Consumer packaging

#### Complementary

Surge current	25 kA per phase
[Ue] rated operational voltage	120/240 V AC
Phase	1 phase
Wiring configuration	3-wire (isolated ground)
[Uc] maximum continuous operating voltage	150 V
Nominal Discharge Current	10 kA
Short-circuit protection	22 kA
Local signalling	1 LED green normal operation
Product destination	Load center
Input voltage	600 V L-N
Height	2.45 in (62.23 mm)
Width	2.89 in (73.41 mm)
Depth	2.06 in (52.32 mm)

#### Environment

NEMA Degree of Protection	NEMA 4X
---------------------------	---------

#### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>