

Product data sheet

Characteristics

SDSA3650

Surge protection device, Surgelogic, 40kA, 600Y/347VAC, 3 phase, 4 wire, NEMA 4X

Main



Product	Surge protection device
Range	Surgelogic

Complementary

Voltage Rating	600Y/347 V AC
MCOV	510 V
SCCR	200 kA
Surge Current	40 kA per phase
Nominal Discharge Current	10 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Local Signalling	Status LED green normal operation
Cable length	24 in (609.60 mm)
Height	3 in (76.20 mm)
Width	3.6 in (91.44 mm)
Depth	3.4 in (86.36 mm)

Environment

Ambient Operating	149 °F (65 °C)
Enclosure Rating	NEMA 4X
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4: type I NEC 285: type I CSA C22.2 No 8

Ordering and shipping details

Category	08462-SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	785901210887
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.10 in (7.874 cm)
Package 1 Width	3.90 in (9.906 cm)
Package 1 Length	5.00 in (12.7 cm)

Package 1 Weight	12.48 oz (353.802 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	6.30 in (16.002 cm)
Package 2 Width	13.60 in (34.544 cm)
Package 2 Length	20.50 in (52.07 cm)
Package 2 Weight	21.92 lb(US) (9.943 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------