



SKU: CCL-1-38

UPC: 0783669031423

Features & Benefits:

Description: Copper Compression Lug, Conductor Size 1, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Index Number	I-37
Mounting Hole Type	Thru
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Round
Undrilled	No

Dimensions

Barrel Length (IN)	0.575
Barrel Length (mm)	14.605
Dimension G (IN)	0.335
Dimension G (mm)	8.509
Height (IN)	0.52
Height BX (IN)	2.25
Height (mm)	13.208
Inside Diameter (IN)	0.36
Inside Diameter (mm)	9.144
Length (IN)	1.72
Length (mm)	43.688
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.402
Mounting Hole Diameter (mm)	10.2108
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.46
Outside Diameter (mm)	11.684
Tang Length (IN)	0.71
Tang Length (mm)	18.034
Tang Thickness (IN)	0.1
Tang Thickness (mm)	2.54
Tang Width (IN)	0.655
Tang Width (mm)	16.637
Weight (LB)	0.08

Weight BX (LB)	1.703
Width (IN)	0.655
Width BX (IN)	5
Width (mm)	16.637

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	2 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366903142

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color

Silver

Color Code

Green

Voltage

Voltage Rating

35 kV