



Pass and Seymour  
PlugTail® 20A 125V Hospital-Grade Decorator Duplex Receptacle, White  
Part No. PT26362HGW



PlugTail Registered Decorator Hospital Grade Receptacles, 20A, 125V PlugTail Registered devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.

## Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

No exposed terminals create a finger-safe application before, during and after installation.

Crimped and welded contacts.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

PlugTail™ Connector: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid or stranded, for use with PlugTail Receptacles only

Plated steel wrap strap design for maximum durability and corrosion resistance.

Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger-safe housing.

Auto-ground clip assures positive ground.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## Specifications

### General Info

Product Line	Pass & Seymour	Color	White
UPC Number	785007309744	Country Of Origin	Mexico
Number of Receptacles	2	Features	Decorator Style
Outlet Type	Hospital Grade	Application Sector	Commercial, Healthcare

Wall Plate Included	No	Standard	cULus UL498, FEDSPEC
Warranty Type	1-Year Limited Warranty		
<b>Dimensions</b>			
Product Width US	1.5 in	Product Depth US	0.625 in
Product Height US	2.75 in		
<b>Listing Agencies / 3rd Party Agencies</b>			
cULus ListingNumber	E140596	cULus Listed	Yes
<b>Additional Information</b>			
Energy Savings	No		
<b>Technical Information</b>			
Operating Temperature Min	-40 °C	Dielectric Strength	Withstands 2000V minimum
Connection Location	Back Only	Number of Wires	3
Operating Temperature Max	60 °C	Amperage	20 A
Number of Poles	Double Pole	Wire Size	12 AWG
Indoor/Outdoor	Indoor	NEMA Configuration Code	5-20R
Operating Temperature	-40°-60°C	Number of Phases	3
Wire Connection Type	PlugTail	Voltage	125.0 V
Environmental Conditions	Flammability: UL94 V2		