SNAPConnect® Heavy Duty Hospital Grade Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 20A, Black

By Hubbell Wiring Device-Kellems
Catalog # SNAPGFTW83BLK

Straight Blade SNAPConnect® Receptacle, GFCI, Tamper and Weather Resistant, Commercial Hospital Grade, Self-Test, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R.

Features

- Audible SNAP, indicates solid connection
- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® Self-Test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired

Application

- Commercial Hospital Grade

General

Catalog Number	SNAPGFTW83BLK
Color	Black
Environmental Conditions	Weather Resistant
Item Type	Self test GFCI receptacle
Material	Nylon
Series	Hospital Grade
Size	4.12 in x 1.75 in x 1.48 in
Specifications	• Base - Nylon • Face - Nylon • Contacts - Brass • Mounting Screws - Stainless Steel • Mounting Strap - Brass • Power Contacts - Brass
Type	Tamper-Resistant, Weather Resistant
UPC	783585746272

Dimensions

Dimensions	1.48 in x 1.75 in x 4.12 in

Height	4.12 in
Length	1.48 in
Width	1.75 in

Electrical Ratings

Current / Amperage Rating	20 A
Phase	Single Phase
Voltage Rating	125 VAC
Wattage	2500 W

Conductor Related

Wire Size	SNAPConnect

Certifications And Compliance

Industry Standard(s)	UL 943 and Meets All NEC® Requirements
Nema Rating	5-20R

Logistics

Carton Quantity	10

Product Assets

Catalog Page - WDK A-17 Catalog Page
Catalog Page - WDK K-7 Catalog Page
Catalog Page - WDK L-5 Catalog Page
Catalog Page - WDK L-14 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - M14625_ACAD
Installation Manuals - PD2986
Sales Drawings - M14625
Specifications - SNAPGFTW83BLK
Warranty - Industrial & Commercial Products

HUBBELL A Hubbell brand

WDK-SNAPGFTW83BLK-SPEC-EN | REV 1/2025