

Surge Protective Devices,
SPIKESHIELD Hospital Grade Surge
Suppression Receptacle, Duplex,
20A 125V, 5-20R, Gray

By Hubbell Wiring Device-Kellems
Catalog # [HBL8362GYSA](#)

Surge Protective Devices, SPIKESHIELD Hospital Grade Surge
Suppression Receptacle, Duplex, 20A 125V, 5-20R, Gray

Features

- High-impact nylon face resists breakage
- Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol for visual identification of surge suppression receptacle

Application

- Decorator Duplex with Light and Alarm

Performance

- Electrical - Frequency - 60Hz
- Electrical - Protection Modes - Normal and Common Modes
- Electrical - Response Time - Approximately 5 ns
- Electrical - Transient Suppression - Peak Energy (10 X 100 Qs) Peak Current (8 X 20 Qs)
- Electrical - Voltage - 120V AC + 10% - 15%
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

General

Catalog Number	HBL8362GYSA
Color	Gray
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED and Audible Alarm
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Hospital Grade
Specifications	• Base Material - Nylon



Type	Duplex
UPC	783585060453
Contact Design - Tandem Modified Bypass	
Face Material - Nylon	
Mounting Screws - Steel-Zinc Plated	
Power Contacts - .031" (.8) Brass	

Dimensions

Display Size	Standard
--------------	----------

Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current / Amperage Rating	20 A
Current Rating	20 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

Certifications And Compliance

Industry Standard(s)	• CSA Certified to Specification C22.2 No. 42 • Listed to UL Standards 498 Receptacles • UL Listed File E2186
Nema Rating	5-20R

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - WDK M-13 Catalog Page](#)
[Catalog Page - WDK I-4 Catalog Page](#)
[Catalog Page - WDK L-16 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)

Engineering Drawing - HBL8362GYSA AutoCAD Drawing
Installation Manuals - WIRING_PD1152_INSTALLINST
Literature - Duct Products Guide
Literature - SpikeShield® Power Quality Surge Protective
Devices

Literature - Healthcare Application Guide
Sales Drawings - WDK_HBL8362_DRAWING_PDF
Specifications - HBL8362GYSA
Warranty - Industrial & Commercial Products



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
WDK-HBL8362GYSA-SPEC-EN | REV 1/2025