



**SKU:** CGRC-58

**UPC:** 0783669026979

**Features & Benefits:**

**Description:** Permaground Bronze Ground Rod Clamp, Conductor Range 2-10, Ground Rod Size 5/8in, Rebar Size #5, UL

## Specs

### Additional Class Attributes

Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

### Conductor Ranges

Conductor Range Solid with Ground Rod	10 Sol
Conductor Range Solid with Rebar	10 Sol
Conductor Range Str with Ground Rod	2 Str - 10 Str
Conductor Range Str with Rebar	4 Str - 10 Str
Conductor Size with Ground Rod	10 Str
Conductor Size with Rebar	10 Sol
Ground Rod Size	5/8
Rebar Size(s) Main	#5 (5/8)

### Dimensions

Drive Size Main	19/32
Drive Type Main	External Hex
Height (IN)	1.63
Height BX (IN)	2
Height (mm)	41.402
Length (IN)	0.928
Length (mm)	23.5712
Weight (LB)	0.119
Weight BX (LB)	6
Width (IN)	0.625
Width BX (IN)	6.188
Width (mm)	15.875

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Material	Cast bronze
Wire Binding Hardware Material	Stainless steel



## Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366902697

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

### Bolt and Screw Sizes

Clamping Bolt Size	3/8-16
Clamping Bolt Size (mm)	96926.4