

# Rigid-IMC-Conduit

## Aluminum Watertight Hubs with Bonding Screw

### Features

- NEMA 2, 3R, 4, 4X, 5, 12, 13, flame-retardant
- Insulated throat
- Rain, oil, and dust tight
- Oversized locknut protects installation from vibration

### Application


- Indoor or outdoor use
- Watertight
- Use to connect rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

### Standard Material

- Aluminum



E148716



Catalog Number	UPC	Trade Size	Unit Ctn.	Ship Case	Weight/Case	A	B
<b>201BAL</b>	87158	<b>1/2"</b>	25	250	23	1.31	1.54
<b>202BAL</b>	87159	<b>3/4"</b>	10	100	13	1.37	1.73
<b>203BAL</b>	87160	<b>1"</b>	10	100	19	1.59	2.04
<b>204BAL</b>	87161	<b>1-1/4"</b>	2	20	6	1.59	2.42
<b>205BAL</b>	87162	<b>1-1/2"</b>		20	7	1.59	2.79
<b>206BAL</b>	87163	<b>2"</b>		10	6	1.59	3.30
<b>207BAL</b>	87164	<b>2-1/2"</b>		5	3	2.44	3.70
<b>208BAL</b>	87165	<b>3"</b>		5	5	2.44	4.39
<b>209BAL</b>	87166	<b>3-1/2"</b>		5	7	2.44	4.88
<b>210BAL</b>	87167	<b>4"</b>		1	2	2.44	5.50