



SKU: ASL-750

UPC: 0783669010190

Features & Benefits:

Description: Aluminum Stacking Adapter, Conductor Range 1/0-750, Tin Plated, UL

Specs

Additional Class Attributes

| | |
|--------------------------|--------|
| Barrel Marking | Hard |
| Flared End | No |
| Mounting Method | Bolted |
| Number of Mounting Holes | 2 |
| Sight Window | No |
| Slotted | No |

Dimensions

| | |
|------------------------|--------|
| Height (IN) | 1.25 |
| Height BX (IN) | 2 |
| Length (IN) | 3 |
| Max Insulation OD (IN) | 1.372 |
| Weight (LB) | 0.2287 |
| Weight BX (LB) | 2.434 |
| Width (IN) | 1 |
| Width BX (IN) | 6.1875 |

Material and Finish

| | |
|---------------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish Material | Tin |
| Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 10 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | 0-000-1 |
| UPC Code | 78366901019 |



Bolt and Screw Sizes

| | |
|-------------------------|------------|
| Mounting Bolt/Stud Size | 1/2 to 5/8 |
|-------------------------|------------|

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | NA |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator | IND |
| UL Control Number | 453G |
| UL / CULUS Specification | UL 486A/B Listed |
| UL File Number | E6207 |

Environment and Temperature

| | |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

Color

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Conductor Ranges

| | |
|--|---------------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | 750 kcmil - 1/0 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 750 kcmil - 1/0 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |

Voltage

| | |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|