



SKU: GBL-1/0

UPC: 0783669960105

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 1/0-14, Tin Plated

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Kit Hardware Part #	GBL-MH3
Number of Conductors	1
Number of Mounting Holes	1
Number of Ports / Wireways	1
Wire Orientation	NA

Dimensions

Dimension G (IN)	0.44
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	1.16
Height BX (IN)	2
Height (mm)	29.464
Length (IN)	1.63
Length (mm)	41.402
Tang Thickness (IN)	0.19
Weight (LB)	0.073
Weight BX (LB)	3.807
Width (IN)	0.63
Width BX (IN)	6.1875
Width (mm)	16.002

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Material	Aluminum
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Stranded
-----------------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366996010

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Wire Binding Torque	1/0 - 6 AWG = 45

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440