

### Conduit Unions UNF & UNY Unions

## 1-1/4 INCH FEMALE-TO-FEMALE (F/F) ALUMINUM UNF UNION

ISO  
9001:2015  
CERTIFIED



**Catalog Number** PRUNF405SA  
**UPC** 784011219292

### Description

PVC coated UNF unions are used to connect conduit to conduit or to allow for future changes to the conduit system. Female threads are provided at each end.

### Application

- Applicable for Hazardous Locations

### Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

### General Information

Trade Size	1-1/4
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane


### Dimensions

Length (Inches)	2.25
Max Diameter (Inches)	3

### Standards

CSA	C22.2 No. 30
NEC/CEC	Class I, Division 1 & 2, Groups C, D
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class III
NEC/CEC	Class II, Division 1, Groups E, F, G
UL 1203	E476062

### Technical Specification Documents



SAFETY US  
E476062



Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Installer Certification and Tools	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Chemical Resistance Charts	AVAILABLE ON WEBSITE
----------------------------	----------------------

Performance Specifications	AVAILABLE ON WEBSITE
----------------------------	----------------------

#### **Technical Information**

Fitting Configuration	F/F
-----------------------	-----

Fitting Type	UNION
--------------	-------

Product Category	HAZARDOUS LOCATION FITTING
------------------	----------------------------

Product Family	Conduit Unions UNF & UNY Unions
----------------	---------------------------------

Rating	Hazardous Location
--------	--------------------