



SKU: TTGC-2

UPC: 0783669233698

Features & Benefits:

Description:Permaground Bronze Transformer Tank Ground Connector, Conductor Range 2/0-8 Sol, 1/2-13 Bolt Size, 1-51/64in Height

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Perpendicular

Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	2
Length (IN)	0
Mounting Bolt/Stud Size (mm)	30810.2
Weight (LB)	0.208
Weight BX (LB)	5.347
Width (IN)	0
Width BX (IN)	6.188

Material and Finish

Clamping Hardware Finish	NA
Clamping Hardware Material	Steel
Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Cast bronze

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	3/8
Clamping Bolt Size (mm)	965.2
Clamping Bolt Torque	NA
Mounting Bolt/Stud Size	1/2-13
Number of Wire Binding Screws per Port	1

Wire Binding Screw Size	NA
-------------------------	----

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366923369

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Bronze
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	2/0 Sol - 8 Sol