

Product availability : Stock - Normally stocked in distribution facility



Price* : 217.00 USD



Main

Bezel material	Chromium plated metal
Control button type	Standard push-button
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor
Operator additional information	Without guard
Range of product	K

Complementary

Line Rated Current	10 A
Accessory / separate part destination	Illuminated push-button
Cap/Operator or lens colour	Red
Contact operation	Standard fingersafe
Contacts type and composition	1 NO + 1 NC
Electrical connection	Screw clamp terminal
Light block supply	Via transformer 120 V AC 50/60 Hz
Marking	Unmarked
Mounting support	Panel
Operator position information	2 positions
Operator profile	1 projecting push-button
Permissible voltage	<= 600 V
Shape	Round head
Size	30 mm
Type of operator	Momentary
Utilisation category	AC-15 DC-13

Environment


NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13
---------------------------	-------------------------

Product certifications	UL listed file E42259 CCN NKCR CE CSA LR 25490 class 3211 03
------------------------	--------------------------------------------------------------------

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901849759
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5700000000000006
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------