


### 15 and 20 Ampere, 125 Volts

#### SNAPConnect GFCI LED Hospital Grade ● Receptacles


  
15A 125V  
NEMA 5-15R  
UL CSA  
0.5 HP

  
20A 125V  
NEMA 5-20R  
UL CSA  
1 HP

**IP20**  
SUITABILITY


   
Fed. Spec. Meets UL  
Standard 943  
Class A GFCI

Description	Color	Catalog Number	
Hospital Grade SNAPConnect GFCI LED, self-grounding staple, requires connector below, sold separately.	Black	<b>SNAPGF82BLK</b>	<b>SNAPGF83BLK</b>
	Brown	<b>SNAPGF82</b>	<b>SNAPGF83</b>
	Gray	<b>SNAPGF82GRY</b>	<b>SNAPGF83GRY</b>
	Ivory	<b>SNAPGF82I</b>	<b>SNAPGF83I</b>
	Light	<b>SNAPGF82LA</b>	<b>SNAPGF83LA</b>
	Almond	<b>SNAPGF82R</b>	<b>SNAPGF83R</b>
	Red	<b>SNAPGF82W</b>	<b>SNAPGF83W</b>



#### SNAPConnect GFCI LED Hospital Grade ● Tamper and Weather Resistant


Description	Color	Catalog Number	
Hospital Grade SNAPConnect GFCI TR/WR, self-grounding staple, requires connector below, sold separately.	Black	<b>SNAPGFTW82BLK</b>	<b>SNAPGFTW83BLK</b>
	Brown	<b>SNAPGFTW82</b>	<b>SNAPGFTW83</b>
	Gray	<b>SNAPGFTW82GRY</b>	<b>SNAPGFTW83GRY</b>
	Ivory	<b>SNAPGFTW82I</b>	<b>SNAPGFTW83I</b>
	Light	<b>SNAPGFTW82LA</b>	<b>SNAPGFTW83LA</b>
	Almond	<b>SNAPGFTW82R</b>	<b>SNAPGFTW83R</b>
	Red	<b>SNAPGFTW82W</b>	<b>SNAPGFTW83W</b>



Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability. See page Tech-10 for Tamper-Resistant description.


#### SNAPConnect USB Charger Hospital Grade ● TR Receptacles

  
15A 125V  
NEMA 5-15R  
UL CSA  
0.5 HP

  
20A 125V  
NEMA 5-20R  
UL CSA  
1 HP




Description	Color	Catalog Number	
Hospital Grade SNAPConnect USB Charger, tamper-resistant Style Line® decorator duplex receptacle, 15 or 20 Amp, 125 Volt AC with one type A & one type-C USB port, 3 Amp up to 9 Volt USB output.	Black	<b>SNAP8200UACBK</b>	<b>SNAP8300UACBK</b>
	Brown	<b>SNAP8200UAC</b>	<b>SNAP8300UAC</b>
	Gray	<b>SNAP8200UACGY</b>	<b>SNAP8300UACGY</b>
	Ivory	<b>SNAP8200UACI</b>	<b>SNAP8300UACI</b>
	Light	<b>SNAP8200UACLA</b>	<b>SNAP8300UACLA</b>
	Almond	<b>SNAP8200UACR</b>	<b>SNAP8300UACR</b>
	Red	<b>SNAP8200UACW</b>	<b>SNAP8300UACW</b>
Hospital Grade SNAPConnect USB Charger, Tamper-Resistant Style Line decorator duplex receptacle, 15 or 20 Amp, 125 Volt AC with two type-C USB portst, 3 Amp up to 9 Volt USB output.	Black	<b>SNAP8200UCBK</b>	<b>SNAP8300UCBK</b>
	Brown	<b>SNAP8200UC</b>	<b>SNAP8300UC</b>
	Gray	<b>SNAP8200UCGY</b>	<b>SNAP8300UCGY</b>
	Ivory	<b>SNAP8200UCI</b>	<b>SNAP8300UCI</b>
	Light	<b>SNAP8200UCLA</b>	<b>SNAP8300UCLA</b>
	Almond	<b>SNAP8200UCR</b>	<b>SNAP8300UCR</b>
	Red	<b>SNAP8200UCW</b>	<b>SNAP8300UCW</b>




#### SNAPConnect Surge Protection Hospital Grade ● Tamper-Resistant Receptacle with Power Indicating LED

  
15A 125V  
NEMA 5-15R  
UL CSA  
0.5 HP

  
20A 125V  
NEMA 5-20R  
UL CSA  
1 HP



Description	Color	Catalog Number	
Hospital Grade SNAPConnect surge suppression, tamper-resistant, smooth face, duplex receptacle.	Blue	<b>SNAP8262S</b>	<b>SNAP8362S</b>
	Gray	<b>SNAP8262GYS</b>	<b>SNAP8362GYS</b>
	Ivory	<b>SNAP8262IS</b>	<b>SNAP8362IS</b>
	Light	<b>SNAP8262LAS</b>	<b>SNAP8362LAS</b>
	Almond	<b>SNAP8262RS</b>	<b>SNAP8362RS</b>
	Red	<b>SNAP8262WS</b>	<b>SNAP8362WS</b>
	White		



#### SNAPConnect Right Angle Pigtailed Connector

Description	Wire Type	Catalog Number
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; polycarbonate housing material with WAGO terminals.	Solid Stranded	<b>SNAP1RNM2</b> <b>SNAP2RNM2</b>

Note: See page Tech-10 for Tamper-Resistant, Weather Resistant and LED Power Indicators descriptions.

Dimensions in Inches (mm)