

Product data sheet

Specifications



Contactor, Definite Purpose, replacement coil, 220/240VAC 50/60Hz, for 8910DPA 50A and 60A contactors, 2 and 3 poles

9998DA2V09

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Coil
Accessory / separate part destination	8910DPA contactor

Complementary

[Ue] rated operational voltage	208/240 V AC 60 Hz 220 V AC 50 Hz
inrush power in VA	109 VA
Average consumption	10 VA
Height	3.27 in (83.06 mm)
Width	2.56 in (65.02 mm)
Depth	3.67 in (93.22 mm)

Ordering and shipping details

Category	US1CP1B21752
Discount Schedule	CP1B
GTIN	785901081456
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.700 in (4.318 cm)
Package 1 Width	2.600 in (6.604 cm)
Package 1 Length	3.500 in (8.890 cm)
Package weight(Lbs)	2.720 oz (77.111 g)

Contractual warranty

Warranty	18 months
----------	-----------


Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Dimensions Drawings

Approximate Dimensions

