



## T5461-E

Tamper-Resistant Single Receptacle, 20 Amp 250 Volt, Black

Single Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 250 Volt, Back and Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - Black


Leviton's 250 Volt Tamper-Resistant Receptacles are the industry's first and only solution to the revisions of the NEC Article 406.12!

- Brass self-grounding clip is permanently staked on for secure and reliable performance
- Tamper-resistant shutters
- Accommodates back and side wiring
- Face made of impact-resistant engineering polymer

Color :  Black

UPC Code : 078477649992

Country Of Origin : Mexico

NEMA :  6-20R

### Available Colors :



Brown



Gray



Ivory



Light Almond



White

### Technical Information

#### Electrical Specifications

**Amperage** : 20 A

**Dielectric Voltage** : 2000 VAC

**Grounding** : Self-Grounding

**HP Rating** : 2 HP

**Pole** : 2

**Temperature Rise** : Max 30 C

**Voltage** : 250 VAC

**Wire** : 3

#### Environmental Specifications

**Flammability** : Rated V-2 per UL 94

**Operating Temperature** : Maximum Continuous 75°C, minimum -40°C (w/o impact)

#### Material Specifications

**Body Material** : Nylon

**Face Material** : PBT

**Ground Contacts** : Phosphor Bronze

**Grounding Screw** : #8 Brass

**Line Contacts** : Brass Triple Wipe 0.040"

**Mounting Screws** : #6 Plated Steel

**Mounting Strap** : Galvanized Steel

**Tamper Resistant Shutter Mechanism** : Thermoplastic

**Terminal Clamps** : Galvanized Steel

**Terminal Screws** : #10 Brass

#### Mechanical Specifications

**Product ID** : Ratings are Marked on Device

#### **Strap Construction :**

**Terminal Accom.** : #14-#10 AWG Solid or Stranded

**Termination** : Back & Side Wire

#### Product Features

**Color** : Black

**Device Type** : Single Receptacle Outlet

**Feature** : Tamper-Resistant, Smooth Face, RoHS Compliant

**Grade** : Heavy-Duty Industrial Specification Grade

**NEMA** : 6-20R

#### Standards & Certifications

**NEMA Rating** : WD-1 and WD-6

**Standards and Certifications** : UL 498; CSA C22.2, No. 42; Fed Spec WC-596; NOM

#### Warranty

**Warranty** : 10-Year Limited

### SPECIFICATION SUBMITTAL

|                                     |   |
|-------------------------------------|---|
| JOB NAME:<br><input type="text"/>   | CATALOG NUMBERS:<br><input type="text"/> <input type="text"/> |
| JOB NUMBER:<br><input type="text"/> | <input type="text"/> <input type="text"/>                     |

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

