

Catalog Number: RC45
Product ID: 7TAA267310R0010
UPC Number: 78378605116
Status: Active



Representative

Aluminum 12 inch Full-Tension Distribution Compression Splice for Wire Range: 4ACSR(6/1,7/1), 4AAAC(7), 4 5005(7), 4AAC(7), Mechanical Dies: 5/8-1, 635, BG, W-BG, W-243, 5/8-1, 635, Hydraulic Dies: B24EA, 243, 687, 5/8-1, 635

UNSPSC Specifications

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Compression Connector / Splice
Special Features	Center stop assures proper conductor positioning. External end taper provides conductor stress relief, ease of stringing and corona protection. Internal end chamfer allows easy conductor insertion and prevents sharp edge contact with conductor. Replaces two-piece splices. Type RC Single Sleeve, Full Tension Splice for ACSR, AAAC, 5005 and AAC Conductor.
Application	Distribution Compression Connector
Standard	ANSI C119.4
Size	12 inch
Connection	compression
Conductor Range	Wire Range: 4ACSR(6/1,7/1), 4AAAC(7), 4 5005(7), 4AAC(7)
Number Of Conductors	2
Material	Aluminum
Insulation	None
Mounting	None

Packaging

Outer Quantity	25
Outer Dimensions (inches)	15.1x5.4x5.5
Weight Uom	35 lbs. per 100

Documents / Support Tools

SDS US 1	sds-00054-tb2
Technical Data Sheet US	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com