



BDBLHC263501, 1-Pole Power Distribution Block

By Burndy
 Catalog # [BDBLHC263501](#)

BURNDY® VERSIPOLE™ Power Distribution Block



Features

- VERSIPOLE Configurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Application

Suitable for use with aluminum or copper conductors providing maximum versatility

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - AL Str Run	<ul style="list-style-type: none"> • 6 • 4 • 3 • 2 • 1 • 1/0 • 2/0 • 3/0 • 4/0 • 250 • 266.8 • 300 • 336.4 • 350
Conductor - AL Str Run Range	6-350
Conductor - AL Str Tap	<ul style="list-style-type: none"> • 12 • 10 • 8 • 6

	<ul style="list-style-type: none"> • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - AL Str Tap Range	14-2/0
Conductor - Copper Str Run	<ul style="list-style-type: none"> • 6 • 5 • 4 • 3 • 2 • 1 • 1/0 • 2/0 • 3/0 • 4/0 • 250 • 300 • 350
Conductor - Copper Str Run Range	6-350
Conductor - Copper Str Tap	<ul style="list-style-type: none"> • 14 • 12 • 10 • 9 • 8 • 7 • 6 • 5 • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - Copper Str Tap Range	14-2/0
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Run • CU C Str-Run • AL C Str-Tap • CU C Str-Tap
Number Of Poles	1
Current	
Rating - Minimum Voltage	600

Amperage Rating 620 A

Dimensions

Dimension - L Length Overall mm 69
Dimension - Height inch 3.55
Dimension - Height mm 90.2 mm
Width 4.75 in
Dimension - Width inch 5.70 in
Dimension - Width mm 145 mm
Length 2.73 in
Dimension - Length Overall inch 2.73
Height 3.55 in
Dimensions 2.73 in x 4.75 in x 3.55 in

General

Trade Name VERSIPOLE™
Insulation Y



Sub Brand VERSIPOLE
Plated Y
Type BDBLH
UPC 12 Digit 781810646052
UPC 14 Digit GTIN 00781810646052
Material Aluminum
Plating Type Tin
UPC 781810646052

Logistics

Minimum Pack Quantity 1
Carton Quantity 18
Pallet Quantity 648

Operational

Temperature Rating 194° F

Product Assets

[Catalog \[English\]](#)