

Product data sheet

Specifications



EasyLogic PM2210, Power & Energy meter, Total Harmonic, LCD display, Pulse, class 1

METSEPM2210

Product availability: Stock - Normally stocked in distribution facility

Main

Range	EasyLogic
Product name	EasyLogic PM2200
Product or Component Type	Power meter
Device short name	PM2210

Complementary

Device Application	Sub billing Power monitoring
Power quality analysis	total harmonic distortion
Type of measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
Metering type	Voltage U, U21, U32, U13, V, V1, V2, V3 Unbalance current Calculated neutral current Apparent power S, S1, S2, S3 Peak demand currents Current I, I1, I2, I3 Active, reactive, apparent energy (signed, four quadrant) Active power P, P1, P2, P3 Reactive power Q, Q1, Q2, Q3 Peak demand power PM, QM, SM Demand power P, Q, S
Accuracy class	Class 1 active energy IEC 62053-21 Class 1 reactive energy IEC 62053-24
Measurement accuracy	Apparent power +/- 1 % Active energy +/- 1 % Reactive energy +/- 1 % Active power +/- 1 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
Measurement current	5...6000 mA
Measurement voltage	35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT
Frequency measurement range	45...65 Hz
[Us] rated supply voltage	44...277 V AC 45...65 Hz +/- 10 % 44...277 V DC +/- 10 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Network Frequency	60 Hz 50 Hz
Ride-through time	100 ms 120 V AC typical 400 ms 230 V AC typical 50 ms 125 V DC typical
Line Rated Current	1 A 5 A
Maximum power consumption in VA	6 VA 277 V AC
Maximum power consumption in W	3.3 W power lines (AC)) 2 W 277 V power lines (DC))
input impedance	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)
Tamperproof of settings	Protected by access code
Display Type	Backlit LCD
Display colour	Monochrome
Display Resolution	128 x 128 pixels
Demand intervals	Configurable from 1 to 60 min
Information displayed	Demand current past value) Demand current present value) Demand power past value) Demand power present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude
Control type	4 x button
Local signalling	Red LED output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED module operating (RUN)
Number of inputs	0
Number of Outputs	1 pulse
POP parameter	20 ms 5...40 V DC, 20 mA 1...9999000 pulse/ k_h (kWh, kVAh, kVARh)
Impulse duration	20 ms
Communication port protocol	POP
Sampling rate	64 samples/cycle
Cybersecurity	Enable/disable communication ports
Communication Service	Remote monitoring
User Language	German English Chinese Russian Spanish Portuguese French
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 RCM EAC C-tick

Mounting Mode	Clip-on
Mounting position	Vertical
Mounting support	Framework
Provided equipment	1 x Installation guide
Measurement category	Category III 480 V Category II 480...600 V
Electrical Insulation Class	Class II Double insulation
Flame retardance	V-0 conforming to UL 94
Connections - terminals	Current transformer screw connection bottom) 6 Voltage inputs screw connection top) 4
Material	Polycarbonate
Width	3.8 in (96 mm)
Depth	Total : 3.00 in (76.09 mm) Embedded : 2.43 in (61.64 mm)
Height	3.8 in (96 mm)
Product Weight	10.6 oz (300 g)
Compatibility code	PM2210

Environment

Service Life	7 year(s)
IP degree of protection	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
Relative humidity	5...95 % 122 °F (50 °C)
Pollution degree	2
Ambient air temperature for operation	14...140 °F (-10...60 °C)
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Operating altitude	<= 6561.68 ft (2000 m)
Electromagnetic compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC Part 15 class A
Overvoltage category	III

Ordering and shipping details

Category	US10PL109734
Discount Schedule	0PL1
GTIN	3606480800160
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
Package 1 Height	4.724 in (12.000 cm)
Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	4.921 in (12.500 cm)
Package weight(Lbs)	12.451 oz (353.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	15.366 lb(US) (6.970 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	144
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	144.976 lb(US) (65.760 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	129 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	11 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	115 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6599793e-9401-4187-a617-35919522fe23
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	14
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.