

Specifications



Eaton CPP516

Eaton Crouse-Hinds series Arktite CPP plug, 20A, 0.312-0.625" cable diameter, Two-wire, three-pole, Brass contacts, 60 Hz, Style 2, 1 HP, Copper-free aluminum, Factory sealed, Delayed action circuit breaking, 125-250 Vac/18 Vdc

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite CPP plug
CATALOG NUMBER	CPP516
UPC	782274175102
PRODUCT LENGTH/DEPTH	8.38 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	1.75 in
PRODUCT WEIGHT	0.8 lb
PRODUCT TYPE	Plug

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

GROUNDING STYLE	Style 2
AMPERAGE RATING	20A
CONFIGURATION	Two-wire, three-pole
CABLE DIAMETER	0.312-0.625 in
VOLTAGE RATING	125-250 Vac/18 Vdc
HORSEPOWER	1 hp
FREQUENCY RATING	60 Hz
MATERIAL	Copper-free aluminum
CONTACT MATERIAL	Brass
SPECIAL FEATURES	Factory sealed
TYPE	Delayed action circuit breaking

Resources

CATALOGS	Arktite CPS and CPP Explosionproof Receptacles and Plugs catalog page
CERTIFICATION REPORTS	Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors UL certification Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors Canadian certification
INSTALLATION INSTRUCTIONS	IF 285 - CPP Plugs
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CPP516

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

