


KC22B1, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy
Catalog # [KC22B1](#)



Mechanical SERVIT POST™ Connector; Cable to Flat

Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none"> • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG

	• 2 AWG
Conductor - Copper Solid Size Range	2 AWG-10 AWG
Conductor - Copper Str Size Range	3 AWG-10 AWG
Physical Attribute - Number of Conductors Accommodated Total	1

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - Nut Width inch	0.75 in
Dimension - L Length Overall mm	53.8 mm
Dimension - P inch	0.26 in
Dimension - Height fraction	1
Dimension - Height inch	1.00 in
Package Height	0.000 in
Dimension - Height mm	25.4 mm
Dimension - Threads per inch	16
Dimension - B Length fraction	31/32 in
Dimension - B Length inch	0.96 in
Dimension - Body Width inch	0.62 in
Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	2.12 in
Dimension - D inch	1.13 in

Force Related

Stud Installation Torque inch pounds	280 LBS/in
--------------------------------------	------------

General

Trade Name	SERVIT POST™
Sub Brand	SERVIT POST
Plated	N
Type	KC and K2C Series
UPC 12 Digit	781810255056
UPC 14 Digit GTIN	00781810255056
Material	Bronze, Leaded, Commercial
Plating Type	Unplated
UPC	781810255056

Logistics

Minimum Pack Quantity 1
Carton Quantity 50
Pallet Quantity 14850

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved
BRDY-KC22B1-SPEC-EN | REV 1/2026