




PHSW MULTI-PURPOSE PURLIN CLAMP WITH SWIVEL, 1/4" ROD, 1/4" MAX FLANGE

CATALOG NUMBER

PHSW4



CERTIFICATIONS



FEATURES

- Attachment to bottom of purlins and beams to support threaded rod
- Swivel feature option for attachment to purlins under sloped roofs

PRODUCT ATTRIBUTES

Material: Steel
Finish: Electrogalvanized
Rod Size: 1/4"
Flange Thickness: 1/4" Max
B: 3/4" Min
Torque: 30 in lb
Static Load 1: 200 lb
Static Load 2: 160 lb


Nut Included: No

ADDITIONAL PRODUCT DETAILS

A jam nut is required for fire protection applications.

Refer to Static Load 1 when attaching to C and Z purlins. Refer to Static Load 2 when attaching to a flat flange.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--