




SKU: PBHD6-750

UPC: 0783669001242

Features & Benefits:

Description: Aluminum Panelboard Lug, Heavy Duty, Dual Rated, Conductor Range 750-2, 6 Ports, 4 Holes, 3/8in Bolt Size, 1-3/8in Hole Spacing, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	6
Number of Mounting Holes	4
Number of Poles	1
Number of Ports / Wireways	6
Wire Orientation	Perpendicular

Dimensions

Dimension G (IN)	0.38
Dimension G (mm)	9.652
Drive Size Main	1/2
Drive Type Main	Internal Hex
Height (IN)	2.96
Height BX (IN)	3.125
Height (mm)	75.184
Length (IN)	5.005
Length (mm)	127.127
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (IN)	1.38
Mounting Hole Spacing (mm)	35.052
Tang Length (IN)	2.35
Tang Length (mm)	59.69
Tang Thickness (IN)	0.75
Tang Thickness (mm)	19.05
Tang Width (IN)	3.84
Tang Width (mm)	97.536
Weight (LB)	1.504
Weight BX (LB)	1.6379
Width (IN)	3.84
Width BX (IN)	3.875
Width (mm)	97.536

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	15/16
Wire Binding Torque	620

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366900124

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating

35 kV