

Specifications



Eaton DSD925

Eaton Crouse-Hinds series DSD selector switch cover and device sub-assembly, 10A, Feraloy iron alloy, 3 position, 2 circuit, Factory sealed, Maintained contact, 600 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series DSD selector switch cover and device sub-assembly
CATALOG NUMBER	DSD925
UPC	782274776408
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	3.65 lb
PRODUCT TYPE	Selector switch cover and device sub-assembly



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III
NEMA RATING	3 7 9

Resources

CATALOGS	DSD and DSDX Cover and Device Sub-assemblies catalog page
CERTIFICATION REPORTS	DSD Explosionproof Cover and Device Sub-assemblies UL certification DSD Explosionproof Cover and Device Sub-assemblies Canadian certification
INSTALLATION INSTRUCTIONS	IF 1424 - DSD, GFS, CPS and ENR Series Replacement Covers IF 1929 - Toggle Operator for EDS, EDSX, EFD, DSD and DSDX Series IF 899 - EDSX, EDS, EFS, DSDX and DSD Control Stations
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DSD925

Product specifications

VOLTAGE RATING	600 Vac
NORMAL POSITION	3 position, 2 circuit
AMPERAGE RATING	10A
MATERIAL	Feraloy iron alloy
SPECIAL FEATURES	Factory sealed
TYPE	Maintained contact

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

