

Straight Blade Devices, Tamper Resistant, Duplex Receptacle, Hubbell-Pro, Hospital Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Red

By Hubbell Wiring Device-Kellems
Catalog # [8200REDTRA](#)



Straight Blade Devices, Tamper Resistant, Duplex Receptacle, Hubbell-Pro, Hospital Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Red

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Triple wipe contacts
- High impact resistant face with circuit I.D. marking area
- Steel mounting strap

Application

Hubbell-Pro Heavy Duty Hospital Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	8200REDTRA
Color	Red
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Hubbell-Pro

Specifications

- Automatic Self-grounding
 - Staple - Stainless steel
 - Base - PBT
 - Clamping Plate - Plated steel
 - Face - Nylon
 - Ground Contacts - Brass
 - Mounting Screws - Zinc plated steel
 - Mounting Strap - Galvanized steel
 - Power Contacts - Brass
- Smooth Face
Receptacle
783585542195

Dimensions

Dimensions	3.28 in x 1.57 in x 1.15 in
Height	1.15 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	1875 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

- | | |
|----------------------|--|
| Industry Standard(s) | <ul style="list-style-type: none">• Certified to CSA, C22.2, No. 42 File 285• Fed. Spec. W-C-596• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2186 |
|----------------------|--|

- | | |
|-------------|-------|
| Nema Rating | 5-15R |
|-------------|-------|

Logistics

- | | |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Product Assets

- [Catalog Page - WDK A-27 Catalog Page](#)
- [Catalog Page - WDK L-8 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Literature - Tamper-Resistant Receptacles for Healthcare](#)
- [Literature - Heavy Duty Tamper-Resistant Receptacles](#)
- [Literature - Duct Products Guide](#)
- [Literature - Hubbell-Pro Hospital Grade Receptacles](#)
- [Literature - Hubbell-PRO Hospital Grade TR Receptacles](#)
- [Literature - Healthcare Application Guide](#)
- [Specifications - 8200REDTRA](#)
- [Warranty - Industrial & Commercial Products](#)
- [Video - Tamper-Resistant Receptacles](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
WDK-8200REDTRA-SPEC-EN | REV 1/2025