



Wiring Device-Kellems

Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R

By Hubbell Wiring Device-Kellems
Catalog # [2182LTRA](#)



Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Brown

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Triple wipe contacts
- High impact resistant decorator face
- Steel mounting strap

Application

Hubbell-Pro Heavy Duty Hospital Grade

General

Color	Brown
Horsepower - Maximum	1
Indicator(s) Type	Green LED
Item Type	Style Line Decorator Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	<ul style="list-style-type: none">• Electrical - Current Interrupting - Certified for current interrupting at full rated current• Electrical - Dielectric Voltage - Withstands 2,000V minimum• Environmental - Flammability - UL 94V-2• Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)• Mechanical - Product Identification - Ratings are a permanent part of the device• Mechanical - Terminal

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	2500 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none">• Certified to CSA, C22.2, No. 42 File 285• Fed. Spec. W-C-596• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2186
Nema Rating	5-20R

Logistics

Carton Quantity	10
-----------------	----

Product Assets

Catalog Page - Wiring A-22 Catalog page
Catalog Page - Wiring M9 Catalog page
Catalogs - Wiring Full Catalog
Literature - Tamper-Resistant Receptacles for Healthcare
Literature - WLBD026_Duct Products Brochure_WEB
Literature - Hubbell-PRO Hospital Grade TR Receptacles
Literature - Hubbell-Pro Hospital Grade Receptacles
Warranty - Industrial & Commercial Products
Video - Tamper-Resistant Receptacles

Related Products

HBI 8364V - Straight Blade Devices, Male Plug, Valise Series
--

Accommodation - #12-#10 AWG stranded or solid copper wire only	2182REDTRA - Straight Blade Devices, Male Plug, Insulgrip, Hospital Grade, Straight, 2-Pole 3-Wire Grounding, 20A 125V, 5-20P, White, Single Pack
• Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA	2182 - Straight Blade Devices, Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Brown
Series	HBL8315CAT - Straight Blade Devices, Male Plug, Insulgrip, Hospital Grade, Angled, 2-Pole 3-Wire Grounding, 20A 125V, 5-20P, Clear, Single Pack
Style	HBL8315C - Straight Blade Devices, Male Plug, Insulgrip, Hospital Grade, Straight, 2-Pole 3-Wire Grounding, 20A 125V, 5-20P, Black and White, Single Pack
Type	
UPC	
Dimensions	
Dimensions	3.28 in x 1.57 in x 1.15 in
Height	1.15 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
WDK-2182LTRA-SPEC-EN | REV 5/2023