



**SKU:** D167-14

**UPC:** 0783669161991

**Features & Benefits:**

**Description:** Copper Neutral Bar, Conductor Range 4-14 Main, 6-14 Tap, 15 Ports

## Specs

### Additional Class Attributes

|                          |            |
|--------------------------|------------|
| Connection               | Mechanical |
| Mounting Hole Type       | Thru       |
| Number of Conductors     | 1          |
| Number of Mounting Holes | 2          |
| Number of Poles          | 1          |
| Number of Ports Tap      | 14         |

### Dimensions

|                              |                   |
|------------------------------|-------------------|
| Dimension G (IN)             | 2.566             |
| Dimension G (mm)             | 65.1764           |
| Drive Size Main              | NA                |
| Drive Type Main              | Slotted           |
| Height (IN)                  | 0.484             |
| Height BX (IN)               | 2                 |
| Height (mm)                  | 12.2936           |
| Length (IN)                  | 6.75              |
| Mounting Bolt/Stud Size (mm) | 254               |
| Mounting Hole Diameter (IN)  | 0.203             |
| Mounting Hole Diameter (mm)  | 5.1562            |
| Mounting Hole Position (IN)  | 7 & 12            |
| Mounting Hole Spacing (IN)   | 1.984             |
| Mounting Hole Spacing (mm)   | 50.3936           |
| Weight (LB)                  | 0.129588062773854 |
| Weight BX (LB)               | 4.699             |
| Width (IN)                   | 0.344             |
| Width BX (IN)                | 6.1875            |
| Width (mm)                   | 8.7376            |

### Material and Finish

|                                |                               |
|--------------------------------|-------------------------------|
| Conductor Material             | Copper                        |
| Connector Finish               | NA                            |
| Insulation                     | NA                            |
| Material                       | Copper                        |
| Wire Binding Hardware Finish   | Zinc Clear Trivalent Chromate |
| Wire Binding Hardware Material | Steel                         |

## Additional Technical Specifications

|                |       |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

## Bolt and Screw Sizes

|                                        |            |
|----------------------------------------|------------|
| Mounting Bolt/Stud Size                | #10        |
| Number of Wire Binding Screws per Port | 1          |
| Wire Binding Screw Size                | NA         |
| Wire Binding Torque                    | 8 AWG = 25 |

## General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 20 |
| Dual Rated                  | No              |
| NEMA Code                   | 0-000-1         |
| UPC Code                    | 78366916199     |

## Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | NA                                                                                                                  |
| UL / CULUS Specification | UL 467 Listed                                                                                                       |
| UL File Number           | E6207                                                                                                               |

## Color

|       |        |
|-------|--------|
| Color | Copper |
|-------|--------|

## Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | 10 Sol - 14 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | 6 Str - 14 Str  |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |