


BX One Hole Strap




Use:

One hole straps are used to provide support for runs of Armored Cable.

Materials:

- Galvanized Steel
- Zinc Plated

Snap-in Flex



Use:

Snap-in connectors are used to terminate Armored cable.

- No tools needed
- Single unit construction eliminates loose component parts, integral green plastic insulated throat bushing provides maximum protection for wire installation
- No locknut required

Materials:

- Steel

Certification:

 E238299

Anti-Short Bushings



Use:

Anti-short bushings are inserted into the end of Armored Cable and Flexible Metal Conduit in order to protect the conductors from the sharp edges of the raceway where cut.

Materials:

- Plastic

BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Ctn/Case Qty/Qty	Case Wt.
			A	B	C		
Boxed							
9300	09300-4	3/8"	1.27	0.5	0.47	100/1000	13.9
9301	09301-1	1/2"	1.43	0.5	0.47	50/100	1.1

BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
<i>Boxed</i>								
9590	09590-9	1/2"	1.44	0.88	-	50/500	37.5	
9591	09591-6	3/4"	1.69	1.31	-	25/250	36	

BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
9593	09593-0	1/2"	1.63	1.69	-	20/200	20.4	

BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Bag/Case Qty/Qty	Case Wt.
Polybag				
9265	09265-6	0	35/500	15
9266	09266-3	1	35/400	12
9267	09267-0	2	35/300	18
9268	09268-7	3	20/200	16
9269	09269-4	4	16/100	9