

Liquidtight

Flexible Metallic Conduit Coil



Features

- Corrosion resistant steel core for lasting mechanical protection
- Oil Resistant
- Sunlight Resistant
- Smooth interior for easy wire pull-thru

Application

- For use in damp or wet locations, suitable for commercial and industrial use
- EF PVC jacket is oil and sunlight resistant
- Non UL

Standard Material

- EF PVC Jacketed Steel Core Coil wrapped in clear plastic shrink wrapped



Topaz Cat. No.	UPC	Size	Feet Coil	Ship Case	Weight Case	Inside Min (inch)	Inside Max (inch)	Outside Min (inch)	Outside Max (inch)
6100	80414	3/8"	100'	100	16	.484	.504	.689	.709
6101	80415	1/2"	100'	100	26	.622	.642	.819	.839
6102	80417	3/4"	100'	100	31	.815	.835	1.032	1.051
6103	80419	1"	100'	100	44	1.032	1.055	1.287	1.315
6104	80421	1-1/4"	50'	50	46	1.370	1.394	1.630	1.661
6105	80423	1-1/2"	50'	50	35	1.579	1.598	1.866	1.902
6106	80425	2"	25'	25	22	2.020	2.043	2.339	2.374
6107	80427	2-1/2"	25'	25	42	2.480	2.504	2.839	2.874
6108	80429	3"	25'	25	53	3.071	3.102	3.461	3.500
6109	80430	3-1/2"	25'	25	55	3.500	3.540	3.960	4.000
6110	80431	4"	25'	25	57	4.000	4.039	4.457	4.500