

Product data sheet

Specifications



Standard shunt trip release MX, ComPacT NSXm, 125VDC, 110/130VAC 50/60Hz

LV426843

Product availability: Stock - Normally stocked in distribution facility

Main

Range	ComPact
Range of Product	ComPacT NSXm
Device short name	MX
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Opening coil Shunt trip release
Control Type	Standard
[Uc] control circuit voltage	110...130 V AC 50/60 Hz 125 V DC
Range compatibility	ComPact ComPacT NSXm ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.7 Un opening
Response time	< 50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	spring

Ordering and shipping details

Category	US10DE201136
Discount Schedule	0DE2
GTIN	3606485413068
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.6 in (1.5 cm)
Package 1 Width	2.2 in (5.7 cm)
Package 1 Length	2.5 in (6.3 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	1.3 oz (36.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	120
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	17.2 lb(US) (7.8 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	75582d60-9779-4641-a03b-18e996230a58
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
Silicon free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	33
Circularity Profile	End of Life Information
Take-back	No



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.