

# MPU7S40F

Unit substation, Mini Power-Zone, plug on,  
7.5kVA, 1 phase, 480V primary, 120/240V  
secondary, 18kA, A



## Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	A
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	7.5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	QO Load Center interior
Number of Spaces Available	10
Number of Circuits	10
Enclosure Type	NEMA 3R hot-rolled steel

## Complementary

Height	32.90 in (835.66 mm)
Width	13.98 in (355.06 mm)
Depth	11.80 in (299.72 mm)
Product Weight	145.00 lb(US) (65.77 kg)

## Ordering and shipping details

Category	16275-MPZ PLUG ON BRANCH CB
Discount Schedule	PE2
GTIN	785901726067
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	32.91 in (83.6 cm)
Package 1 Width	13.98 in (35.5 cm)
Package 1 Length	11.81 in (30.0 cm)
Package 1 Weight	143.00 lb(US) (64.864 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------