

# Product data sheet

## Characteristics

ZB5AH033

green flush illuminated pushbutton head Ø22  
push-push for integral LED

Product availability : Stock - Normally stocked in distribution facility

Price\* : 24.80 USD



## Main

|                               |                                  |
|-------------------------------|----------------------------------|
| Range of product              | Harmony XB5                      |
| Product or component type     | Head for illuminated push-button |
| Product compatibility         | Integral LED                     |
| Device short name             | ZB5                              |
| Bezel material                | Plastic                          |
| Mounting diameter             | 0.87 in (22 mm)                  |
| Sale per indivisible quantity | 1                                |
| Shape of signaling unit head  | Round                            |
| Type of operator              | Push-push                        |
| Operator profile              | Green flush unmarked             |

## Complementary

|                             |  |
|-----------------------------|--|
| CAD overall width           | 1.14 in (29 mm)  |
| CAD overall height          | 1.14 in (29 mm)  |
| CAD overall depth           | 1.18 in (30 mm)  |
| Product weight              | 0.04 lb(US) (0.017 kg)   |
| Mechanical durability       | 5000000 cycles   |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs   |
| Electrical composition code | M10 <= 2 contacts using single blocks in front mounting with integral LED<br>M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer<br>MF1 <= 2 contacts using single blocks in front mounting with integral LED<br>MR1 <= 2 contacts using single blocks in rear mounting with integral LED<br>M5 <= 2 contacts using single blocks in front mounting with integral LED |

## Environment

|                      |    |
|----------------------|----|
| Protective treatment | TH |
|----------------------|----|

|  |  |
|--|--|
| Ambient air temperature for storage        | -40...158 °F (-40...70 °C)   |
| Ambient air temperature for operation      | -13...158 °F (-25...70 °C)   |
| Class of protection against electric shock | Class II conforming to IEC 60536   |
| IP degree of protection                    | IP66 conforming to IEC 60529   |
| NEMA degree of protection                  | NEMA 13<br>NEMA 4X   |
| Resistance to high pressure washer         | 1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m  |
| IK degree of protection                    | IK05 conforming to IEC 50102   |
| Standards                                  | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14  |
| Product certifications                     | BV<br>CSA<br>DNV<br>GL<br>LROS (Lloyds register of shipping)<br>RINA<br>UL listed  |
| Vibration resistance                       | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                           | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |

### Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule     | CS2                                   |
| GTIN                  | 00785901386346                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 4.0000000000000001E-2                 |
| Returnability         | Y                                     |
| Country of origin     | FR                                    |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|