

# 20A, 125V, 2 Pole, 3 Wire Grounding Extra Heavy Duty SNAPConnect® Receptacles

# HUBBELL

## Features

- Audible SNAP, indicates solid connection
- Reduces installation time
- Fully insulated design

## Ordering Information

|                                     |              |              |                |
|-------------------------------------|--------------|--------------|----------------|
| Description                         | Device Color | UPC          | Catalog Number |
| Specification grade, finder groove. | Black        | 783585247755 | SNAP5362BKA    |

## Listings

UL Listed to UL498 File No. E2186  
Certified to CSA, C22.2, No. 42 File 285  
Fed. Spec. W-C-596  
NEMA® WD-6 Compliant

## Specifications

|                            |                   |
|----------------------------|-------------------|
| Face                       | Nylon             |
| Base                       | PBT               |
| Contacts                   | Brass             |
| Mounting Strap             | Galvanized steel  |
| Auto Self-grounding Staple | Stainless steel   |
| Mounting Screws            | Zinc plated steel |

## Performance

### Electrical

|                      |   |
|----------------------|---|
| Current Interrupting | Receptacle certified for current interrupting at full rated current |
| Dielectric Voltage   | Withstands 2,000V minimum   |

### Mechanical

|                        |  |
|------------------------|--|
| Product Identification | Ratings are a permanent part of the device |
|------------------------|--|

### Environmental

|                       |   |
|-----------------------|---|
| Flammability          | UL 94V-2  |
| Operating Temperature | Maximum continuous 75°C; minimum -40°C (without impact) |



## Accessories

Wallplate or Weatherproof Cover Duplex Opening

## Resources

[eCatalog](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

