

Sealing Locknuts

Steel

Features

- Zinc plated with PVC molded gasket for a watertight seal

Applications


- Indoor or outdoor use
- Use to secure Rigid, IMC conduit or various threaded fittings to a steel outlet box or other metal enclosures, when moisture proof protection is required

Standard Material

- Steel

Standard Finish

- Zinc plated
- PVC gasket



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
711	17450	1/2"	14	50	500	8	1.12	.26	.787 - .797
712	17460	3/4"	14	50	500	11	1.37	.27	.999 - 1.009
713	17470	1"	11-1/2	25	250	10	1.75	.28	1.25 - 1.26
714	17480	1-1/4"	11-1/2	10	100	6	2.06	.32	1.595 - 1.605
715	17490	1-1/2"	11-1/2	10	100	7	2.37	.32	1.837 - 1.847
716	17500	2"	11-1/2	10	100	9	2.87	.32	2.307 - 2.317
717	17510	2-1/2"	8	---	25	3	3.43	.32	2.777 - 2.788
718	17520	3"	8	---	25	5	4.12	.32	3.403 - 3.414
719	17530	3-1/2"	8	---	25	6	4.62	.32	3.892 - 3.904
720	17540	4"	8	---	25	7	5.18	.32	4.399 - 4.411
720A	85017	5"	8	---	5	8	6.67	.50	5.488 - 5.50
720B	17542	6"	8	---	5	11	7.83	.52	6.545 - 6.557