



Pass and Seymour
15A 120V/125V Combination Single-Pole Toggle Switch and Single Receptacle, Light Almond
Part No. 691LA

Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.



Features & Benefits

Easily accessible break-off separate or common feed.

Two devices fit into the space of one.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

One-piece heat-treated triple-wipe brass power contacts.

Grounding combination devices meet NEC Requirements.

Specifications

General Info

Product Line	Pass & Seymour	Color	Light Almond
Finish	Satin	UPC Number	785007691054
Country Of Origin	Mexico	Material	Thermoplastic
Features	Combination	Switch Type	Toggle
Number of Switches	1	Application Sector	Hospitality, Residential
Wall Plate Included	No	Standard	UL20, UL498
Warranty Type	1-Year Limited Warranty	Type	Combination, Outlet, Switch

Dimensions

Product Width US	1.32 in	Product Depth US	0.94 in
------------------	---------	------------------	---------

Product Height US	4.06 in
-------------------	---------

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	140597	cULus Listed	Yes
---------------------	--------	--------------	-----

Technical Information

Load Rating	15 A @ 120/125 VAC	Seismic Tested	No
-------------	--------------------	----------------	----

Contact Configuration	N-0	Operating Cycles	30000
-----------------------	-----	------------------	-------

Connection Location	Side Only	Terminal Accommodation	#14 AWG - #12 AWG
---------------------	-----------	------------------------	-------------------

Number of Gangs	1	Throw Type	Single Throw
-----------------	---	------------	--------------

Amperage	15 A	Number of Poles	Single Pole
----------	------	-----------------	-------------

Requires Neutral Wire	Yes	Indoor/Outdoor	Indoor
-----------------------	-----	----------------	--------

Mounting Type	Wall Box	Location Rating	Dry
---------------	----------	-----------------	-----

Wire Connection Type	Screw Terminals	Voltage	120 VAC, 125 VAC
----------------------	-----------------	---------	------------------

Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	Flammability: UL94 V2
-----------	---	--------------------------	-----------------------
