


Set Screw LR Conduit Bodies



Use:

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket

Certification:

UL E121488 SP LR57925

Standards:


UL 514B
CSA C22.2 No. 18
NEMA FB-1
NEC Article 348

EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
D100-CGV	15600-6	1/2"	4.30	1.30	2.40	-	27	7
D101-CGV	15606-8	3/4"	5.00	1.50	2.60	-	15	7.5
D102-CGV	15612-9	1"	5.80	1.80	2.90	-	14	9
D103-CGV	15618-1	1 1/4"	7.80	2.50	3.70	-	4	5.5
D104-CGV	15624-2	1 1/2"	7.80	2.50	3.90	-	4	6
D105-CGV	15630-3	2"	9.80	3.20	4.70	-	2	4.5
16-CG	15775-1	2 1/2"	10.50	4.40	5.60	-	1	5.6
17-CG	15776-8	3"	10.50	4.50	6.00	-	1	6.5
18-CG	15777-5	3 1/2"	15.47	5.43	7.36	-	1	8.5
19-CG	15778-2	4"	15.47	5.43	7.36	-	1	8.6

* "D" bodies are also threaded for rigid

Set Screw LL Conduit Bodies



Use:

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket

Certification:

UL E121488 SP LR57925

Standards:

UL 514B
CSA C22.2 No. 18
NEMA FB-1
NEC Article 348

EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
D200-CGV	15636-5	1/2"	4.30	1.30	2.40	-	27	7
D201-CGV	15642-6	3/4"	5.00	1.50	2.60	-	15	7.5
D202-CGV	15648-8	1"	5.80	1.80	2.90	-	14	9
D203-CGV	15654-9	1 1/4"	7.80	2.50	3.70	-	4	5.5
D204-CGV	15660-0	1 1/2"	7.80	2.50	3.90	-	4	6
D205-CGV	15666-2	2"	9.80	3.20	4.70	-	2	5.5
26-CG	15779-9	2 1/2"	10.50	4.40	5.60	-	1	5.6
27-CG	15780-0	3"	10.50	4.50	6.00	-	1	6.5
28-CG	15781-2	3 1/2"	15.47	5.43	7.36	-	1	8.5
29-CG	15782-9	4"	15.47	5.43	7.36	-	1	8.6

* "D" bodies are also threaded for rigid

Set Screw LB Conduit Bodies

**Use:**

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket


Certification:

UL E121488 LR57925

Standards:

UL 514B
CSA C22.2 No. 18
NEMA FB-1
NEC Article 348

Set Screw T Conduit Bodies

**Use:**

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket


Certification:

UL E121488 LR57925

Standards:

UL 514B
CSA C22.2 No. 18
NEMA FB-1
NEC Article 348

Set Screw C Conduit Bodies

**Use:**

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket

Certification:

UL E121488 LR57925

Standards:

UL 514B
CSA C22.2 No. 18
NEMA FB-1
NEC Article 348

EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

Boxed

D600-CGV	15708-9	1/2"	4.30	1.30	2.40	-	30	7
D601-CGV	15714-7	3/4"	5.00	1.50	2.60	-	18	7.5
D602-CGV	15720-1	1"	5.80	1.80	2.90	-	16	9
D603-CGV	15726-3	1 1/4"	7.80	2.50	3.70	-	8	5.5
D604-CGV	15732-4	1 1/2"	7.80	2.50	3.90	-	8	6
D605-CGV	15738-6	2"	9.80	3.20	4.70	-	2	5.5
66-CG	18771-0	2 1/2"	10.50	4.40	5.60	-	1	4.5
67-CG	71741-2	3"	10.50	4.50	6.00	-	1	5
68-CG	15787-4	3 1/2"	15.47	5.43	7.36	-	1	9.5
69-CG	71751-1	4"	15.47	5.43	7.36	-	1	8.5

* "D" bodies are also threaded for rigid

EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

Boxed

D700-CGV	15744-7	1/2"	4.30	1.30	2.40	-	16	5
D701-CGV	15750-8	3/4"	5.00	1.50	2.60	-	12	5.5
D702-CGV	15756-0	1"	5.80	1.80	2.90	-	14	9
D703-CGV	15762-1	1 1/4"	7.80	2.50	3.70	-	4	7.5
D704-CGV	15768-3	1 1/2"	7.80	2.50	3.90	-	4	6.5
D705-CGV	15774-4	2"	9.80	3.20	4.70	-	2	5.5
76-CG	15788-1	2 1/2"	10.50	4.40	5.60	-	1	5.6
77-CG	15789-8	3"	10.50	4.50	6.00	-	1	6.5
78-CG	15790-4	3 1/2"	15.47	5.43	7.36	-	1	8.5
79-CG	15791-1	4"	15.47	5.43	7.36	-	1	8.6

* "D" bodies are also threaded for rigid

EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

Boxed

D300-CGV	15672-3	1/2"	4.30	1.30	2.40	-	24	6.5
D301-CGV	15678-5	3/4"	5.00	1.50	2.60	-	18	7.5
D302-CGV	15684-6	1"	5.80	1.80	2.90	-	14	9
D303-CGV	15690-7	1 1/4"	7.80	2.50	3.70	-	8	12
D304-CGV	15696-9	1 1/2"	7.80	2.50	3.90	-	8	11
D305-CGV	15704-1	2"	9.80	3.20	4.70	-	2	5
36-CG	15783-6	2 1/2"	10.50	4.40	5.60	-	1	6.5
37-CG	15784-3	3"	10.50	4.50	6.00	-	1	7.5
38-CG	15785-0	3 1/2"	15.47	5.43	7.36	-	1	9
39-CG	15786-7	4"	15.47	5.43	7.36	-	1	12

* "D" bodies are also threaded for rigid