

# Specifications



## Eaton CDR20034

Eaton Crouse-Hinds series PowerMate CDR receptacle, 200A, Three-wire, four-pole, Style 2, Copper-free aluminum, 600 Vac/250 Vdc

### General specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton Crouse-Hinds series PowerMate CDR receptacle |
| <b>CATALOG NUMBER</b>       | CDR20034   |
| <b>UPC</b>                  | 662276365018                                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 7.88 in  |
| <b>PRODUCT HEIGHT</b>       | 7.19 in  |
| <b>PRODUCT WIDTH</b>        | 7.19 in  |
| <b>PRODUCT WEIGHT</b>       | 11.12 lb   |



Powering Business Worldwide

## Certifications and compliances

|                            |                                  |
|----------------------------|----------------------------------|
| <b>AREA CLASSIFICATION</b> | Ordinary/Non-Hazardous Locations |
| <b>STANDARDS TYPE</b>      | NEC/CEC                          |
| <b>NEMA RATING</b>         | 4X                               |

## Resources

|                                      |  |
|--------------------------------------|--|
| <b>3D CAD DRAWING PACKAGE</b>        | <a href="#">Eaton Crouse-Hinds CDR20034 3D drawing</a>                                       |
| <b>BROCHURES</b>                     | <a href="#">PowerMate Drilling Pin and Sleeve Devices brochure</a>                           |
| <b>CATALOGS</b>                      | <a href="#">PowerMate Drilling Pin and Sleeve Devices catalog page</a>                       |
| <b>CERTIFICATION REPORTS</b>         | <a href="#">PowerMate Drilling Pin and Sleeve Devices UL certification (Receptacles)</a>     |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">IF 1652 - 200A PowerMate Pin and Sleeve Devices</a>                              |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">PowerMate Connectors</a><br><a href="#">Eaton Specification Sheet - CDR20034</a> |

## Product specifications

|                        |                       |
|------------------------|-----------------------|
| <b>AMPERAGE RATING</b> | 200A                  |
| <b>GROUNDING TYPE</b>  | Style 2               |
| <b>CONFIGURATION</b>   | Three-wire, four-pole |
| <b>VOLTAGE RATING</b>  | 600 Vac/250 Vdc       |
| <b>MATERIAL</b>        | Copper-free aluminum  |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

