

Product data sheet

Specifications

SQUARE D



Contactor, Type L, multipole
lighting, replacement coil, 277VAC
60Hz, 8903L 2 to 6 poles, 8903LX
2 to 4 poles

9998L55

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8903 contactor

Complementary

[Ue] rated operational voltage	277 V AC 60 Hz
inrush power in VA	150 VA
Average consumption	30 VA
Height	2.4 in (60.5 mm)
Width	2.1 in (53.6 mm)
Depth	1.5 in (37.1 mm)

Ordering and shipping details

Category	US1CP1021756
Discount Schedule	CP10
GTIN	785901081241
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.100 in (5.334 cm)
Package 1 Width	2.800 in (7.112 cm)
Package 1 Length	3.400 in (8.636 cm)
Package weight(Lbs)	5.440 oz (154.221 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	5.700 in (14.478 cm)
Package 2 Width	11.700 in (29.718 cm)
Package 2 Length	15.700 in (39.878 cm)
Package 2 Weight	9.200 lb(US) (4.173 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

Use Again

Repack and remanufacture

Take-back	No
-----------	----