



Cables and Receptacles

| Device Type | Ratings | Wires | Conductor Colors** | Length (FT) |
|---|---|--|---|--|
|  PH = Double Ended Cable with Male/Female Straight PM = Male Single Ended Straight PN = Male Single Ended 90° PF = Female Single Ended Straight PG = Female Single Ended 90° PQ = Double Ended Cable with Female 90° PR = Double Ended Cable with Male 90° PS = Double Ended Cable with (2) 90° Connectors  RF = Female Receptacle*  RM = Male Receptacle (Inlet)* Example: PH | 10 = 10A - 3W, 4W, 5W 10A - 7W, 9W 7A - 12W up to 600V | 03 04 05 07 09 12 | PV = Green/Yellow Black (all others) | 001 = 1' 005 = 5' 010 = 10' 015 = 15' 020 = 20' 025 = 25' 030 = 30' 035 = 35' 040 = 40' 045 = 45' 050 = 50' |
| | 10 | 04 | PV | 005 |

Note: *1/2" NPT rear thread.

**Other color codes available upon request.

Configurations (Male face view shown, female view is opposite)

| 10 AMP |  |  |  |  |  |
|--------|---|---|---|---|---|
|--------|---|---|---|---|---|

Note: *Reverse key.

Splitters/Tees

| Description | Catalog Number |
|-----------------------------------|-----------------|
| LINKOSITY M/F/F splitter, 3A/4W. | TX0304000304T00 |
| LINKOSITY M/F/F tee, 10A, 2 pole. | TX1002001002T00 |
| LINKOSITY M/F/F tee, 10A, 3 pole. | TX1003001003T00 |
| LINKOSITY M/F/F tee, 10A, 4 pole. | TX1004001004T00 |
| LINKOSITY M/F/F tee, 10A, 5 pole. | TX1005001005T00 |
| LINKOSITY M/F/F tee, 10A, 6 pole. | TX1006001006T00 |



TX1004001004T00

Closure Caps

| Description | For use with Female Receptacle | Male Inlet |
|--|--------------------------------|------------|
| 3A closure cap. | CCM1C | CCF1C |
| 10A closure cap, 2, 3, 4, 4, 5 and 6 pole. | CCMAC | CCFAC |
| 10A closure cap, 7 and 8 pole. | CCMBC | CCFBC |
| 10A closure cap, 9, 10, 12 pole. | CCMCC | CCFCC |



CCFAC

Dimensions in Inches (mm)