



Single-Pole, Single Pilot light, Combination Switch, 15A, 120/125As, White.

Features & Benefits

Easily accessible break-off separate or common feed.

Long-life red neon lamp in pilot light rated 1/25 Watt, 125V.

Side wire #12 and #14 AWG.

Two devices fit into the space of one.

Grounding combination devices meet NEC Requirements. Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

| | | | |
|---------------------|-------------------------|--------------------|--------------------------|
| Product Line | Pass & Seymour | Color | Light Almond |
| Finish | Satin | UPC Number | 785007006100 |
| Country Of Origin | Mexico | Material | Thermoplastic |
| Features | Combination | Switch Type | Pilot, Switch |
| Number of Switches | 1 | Application Sector | Hospitality, Residential |
| Wall Plate Included | No | Standard | UL20 |
| Warranty Type | 1-Year Limited Warranty | Type | Combination |

Dimensions

| | | | |
|------------------|---------|------------------|---------|
| Product Width US | 1.32 in | Product Depth US | 1.15 in |
|------------------|---------|------------------|---------|

| | |
|-------------------|---------|
| Product Height US | 4.06 in |
|-------------------|---------|

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

| | | | |
|-------------|----------------|-----------------------|-----|
| Load Rating | 15 A @ 120 VAC | Contact Configuration | N-0 |
|-------------|----------------|-----------------------|-----|

| | | | |
|------------------|-------|---------------------|-----------|
| Operating Cycles | 30000 | Connection Location | Side Only |
|------------------|-------|---------------------|-----------|

| | | | |
|------------------------|-------------------|-----------------|---|
| Terminal Accommodation | #14 AWG - #12 AWG | Number of Gangs | 1 |
|------------------------|-------------------|-----------------|---|

| | | | |
|------------|--------------|----------|------|
| Throw Type | Single Throw | Amperage | 15 A |
|------------|--------------|----------|------|

| | | | |
|-----------------|-------------|-----------------------|-----|
| Number of Poles | Single Pole | Requires Neutral Wire | Yes |
|-----------------|-------------|-----------------------|-----|

| | | | |
|----------------|--------|---------------|----------|
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box |
|----------------|--------|---------------|----------|

| | | | |
|-----------------|-----|----------------------|-----------------|
| Location Rating | Dry | Wire Connection Type | Screw Terminals |
|-----------------|-----|----------------------|-----------------|

| | | | |
|---------|---------|-----------|--|
| Voltage | 120.0 V | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
|---------|---------|-----------|--|

| | |
|--------------------------|-----------------------|
| Environmental Conditions | Flammability: UL94 V2 |
|--------------------------|-----------------------|
