



SKU: PDBU-412-500-1

UPC: 0783669594928

Features & Benefits:

Description:Power Distribution Block, Dual Rated, Line Conductor Range 500-4, Load Range 4/0-6, 4 Ports Per Pole Line Side, 12 Ports Per Pole Load Side, 1 Pole, UL, CSA

Specs

Additional Class Attributes

Block Size	W
Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	16
Number of Poles	1
Number of Ports Per Pole Primary	4
Number of Ports Per Pole Secondary	12

Dimensions

Drive Size Main	3/8
Drive Size Tap	5/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	4.69
Height BX (IN)	4.75
Height (mm)	119.126
Length (IN)	6.335
Length (mm)	160.909
Mounting Hole Diameter (IN)	0.281
Mounting Hole Spacing (IN)	3
Mounting Hole Spacing (mm)	76.2
Weight (LB)	2.489
Weight BX (LB)	2.7974
Width (IN)	4
Width BX (IN)	5
Width (mm)	101.6

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Enclosure Material	Valox
Insulation Material	NA
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum



Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366959492

Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
RUS Listed	No
UL Control Number	45U4
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E112158

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 4 Str
Conductor Range AL Stranded (Secondary, tap, load)	4/0 Str - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	4/0 Str - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	1520 Amps
Conductor Type	Solid

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Flammability Rating	NA
Temperature Rating	90°C

