

Specifications

Eaton CPP516

Eaton Crouse-Hinds series Arktite CPP plug, 20A, 0.312-0.625" cable diameter, Two-wire, three-pole, Brass contacts, 60 Hz, Style 2, 1 HP, Copper-free aluminum, Factory sealed, Delayed action circuit breaking, 125-250 Vac/18 Vdc

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite CPP plug
CATALOG NUMBER	CPP516
UPC	782274175102
PRODUCT LENGTH/DEPTH	8.38 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	1.75 in
PRODUCT WEIGHT	0.8 lb
PRODUCT TYPE	Plug



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

GROUNDING STYLE	Style 2
AMPERAGE RATING	20A
CONFIGURATION	Two-wire, three-pole
CABLE DIAMETER	0.312-0.625 in
VOLTAGE RATING	125-250 Vac/18 Vdc
HORSEPOWER	1 hp
FREQUENCY RATING	60 Hz
MATERIAL	Copper-free aluminum
CONTACT MATERIAL	Brass
SPECIAL FEATURES	Factory sealed
TYPE	Delayed action circuit breaking

Resources

CATALOGS [Arktite CPS and CPP Explosionproof Receptacles and Plugs catalog page](#)

CERTIFICATION REPORTS [Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors UL certification](#)
[Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors Canadian certification](#)

INSTALLATION INSTRUCTIONS [IF 285 - CPP Plugs](#)

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - CPP516](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

