

Project:

Type:

Prepared By:

Date:



- Features and Benefits
- 3-Lead Surge Protector
 - Protects Against Surges According to IEEE C62.41.2
 - Surge Location Rated Category C3
 - 10KA and 10KV
 - IP67 Rated for Wet Locations
 - High Temperature/Flameproof Enclosure (194°F/90°C Max. Surface Rating)
 - RoHS Compliant
 - UL Recognized (UL1449)
 - Parallel Wiring

Technical Specifications	
Performance Nominal Operating Voltage: 110 - 277V AC Rated Voltage (max. continuous voltage): 300V Nominal Discharge Current: 5kA Max Discharge Current: 10kA Nominal Discharge Voltage: 10kV Maximum Discharge Voltage: 15kV Response Time: 25ns Max. Backup Fuse: 16A gL/gG Cross-Section Area: 1.5mm² flexible	Mounting: Custom Size: 97 x 45 x 22mm Outer Casting Protection Grade: IP65 Electrical Voltage Protection Level: 1.1kV Operating Temperature Range (Parallel Wiring): -40°C - 70°C Operating Temperature Range (Through Wiring): -40°C - 70°C Construction Enclosure Material: Thermoplastic Compliance California Energy Commission (CEC) Status: Lawful for Sales in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	0	0	0	0
PALLET	5880	0	0	0