

Turnlok Registered Connector 3-Wire 30A 3-Phase 250V



## Features & Benefits

- Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire. Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.
- Raised ribs provide non-slip gripping profile for turning to lock and unlock. Double dovetail design provides superior protection against cord pull-out forces.
- Impact- and corrosion-resistant durable nylon 6 shell material. Rounded back contour reduces snags and hang-ups on the job site.
- Scallop shell design provides non-slip gripping surface for insertion and withdrawal. Visible stamped NEMA configuration and device rating.
- New-design external cord grips provide visible assurance of safe and proper cord retention. Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.

## Specifications

### General Info

Product Line	Pass & Seymour	Color	Black
UPC Number	785007113013	Country Of Origin	Mexico
Features	Corrosion Resistant	Application Sector	Commercial
Standard	UL 498	Warranty Type	1-Year
Type	Connector		

### Dimensions

Product Width US	2.2 in	Product Length US	3.33 in
------------------	--------	-------------------	---------

---

## Additional Information

---

Product Environmental Profile      Yes

---

## Technical Information

---

Connector Style                      Locking                      Flanged                      No

---

Terminal Accommodation              #18 AWG - #10 AWG              Number of Wires              3

---

Amperage                      30 A                      Number of Poles              3-Way

---

Indoor/Outdoor                      Indoor                      NEMA Configuration Code              L11-30R

---

Number of Phases                      3                      Voltage                      250.0 V

---