



Wiring Device-Kellems

# Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R

By Hubbell Wiring Device-Kellems  
Catalog # [2182GYLTRA](#)



Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Gray

## Features

- Tamper-resistant shutter complies with national electrical code requirements
- Triple wipe contacts
- High impact resistant decorator face
- Steel mounting strap

## Application

Hubbell-Pro Heavy Duty Hospital Grade

## General

Color	Gray
Horsepower - Maximum	1
Indicator(s) Type	Green LED
Item Type	Style Line Decorator Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	<ul style="list-style-type: none"><li>• Electrical - Current Interrupting - Certified for current interrupting at full rated current</li><li>• Electrical - Dielectric Voltage - Withstands 2,000V minimum</li><li>• Environmental - Flammability - UL 94V-2</li><li>• Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)</li><li>• Mechanical - Product Identification - Ratings are a permanent part of the device</li><li>• Mechanical - Terminal</li></ul>

## Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	2500 W

## Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG

## Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>• Certified to CSA, C22.2, No. 42 File 285</li><li>• Fed. Spec. W-C-596</li><li>• NEMA® WD-6 Compliant</li><li>• UL Listed to UL498 File No. E2186</li></ul>
Nema Rating	5-20R

## Logistics

Carton Quantity	10
-----------------	----

## Product Assets

<a href="#">Catalog Page - Wiring A-22 Catalog page</a>
<a href="#">Catalog Page - Wiring M9 Catalog page</a>
<a href="#">Catalogs - Wiring Full Catalog</a>
<a href="#">Installation Manuals - WIRING_PD2504_INSTALLINST</a>
<a href="#">Literature - Tamper-Resistant Receptacles for Healthcare</a>
<a href="#">Literature - WLBD026_Duct Products Brochure_WEB</a>
<a href="#">Literature - Hubbell-PRO Hospital Grade TR Receptacles</a>
<a href="#">Literature - Hubbell-Pro Hospital Grade Receptacles</a>
<a href="#">Warranty - Industrial &amp; Commercial Products</a>
<a href="#">Video - Tamper-Resistant Receptacles</a>

## Related Products

	Accommodation - #12-#10 AWG stranded or solid copper wire only	HBL8300GY - Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole3-Wire Grounding, 20A 125V, 5-20R, Gray, Single Pack
	<ul style="list-style-type: none"> <li>• Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA</li> </ul>	HBL8300HG - Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Gray, Single Pack
		HBL8300SGGYA - Straight Blade Devices, Receptacles, Duplex, Safety Grade Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Gray, Single Pack
Series	Hubbell-Pro	2182BKLTRA - Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R
Style	Style Line decorator	2182IVLTRA - Straight Blade Devices, Tamper Resistant Decorator Duplex Receptacle, Hospital Grade, Hubbell-Pro, LED Indicator, 20A 125V, 5-20R
Type	Duplex Receptacle	
UPC	783585541945	

## Dimensions

Dimensions	3.28 in x 1.57 in x 1.15 in
Height	1.15 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
WDK-2182GYLTRA-SPEC-EN | REV 5/2023