

Product data sheet

Specifications



Undervoltage release (MN), TeSys Deca, 200V AC 50 Hz

GVAU207

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys TeSys Deca
Product or Component Type	Undervoltage release
Device short name	GVAU
[Uc] control circuit voltage	200 V AC 50 Hz 200...220 V AC 60 Hz

Complementary

Range compatibility	TeSys GV2ME TeSys GV2LE TeSys GV2L TeSys GV2P TeSys GV3L TeSys GV3P TeSys Deca
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	690 V AC IEC 60947-1 600 V AC UL 60947-4-1 600 V AC CSA C22.2 No 60947-4-1
Threshold tripping voltage	0.7...0.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W
Hold-in Power Consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W
Operating time	10...15 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	screw clamp terminals 1 0.002...0.004 in² (1...2.5 mm²)solid screw clamp terminals 2 0.002...0.004 in² (1...2.5 mm²)solid screw clamp terminals 1 0.001...0.004 in² (0.75...2.5 mm²)flexible without cable end screw clamp terminals 2 0.001...0.004 in² (0.75...2.5 mm²)flexible without cable end screw clamp terminals 1 0.001...0.002 in² (0.75...1.5 mm²)flexible with cable end screw clamp terminals 2 0.001...0.002 in² (0.75...1.5 mm²)flexible with cable end
Tightening torque	< 1.4 N.m screw clamp terminals
Mechanical durability	10000 cycles with GV3P and GV3L 30000 cycles with GV2ME and GV2P
Quantity per Set	Set of 10
Height	3.5 in (89 mm)
Width	0.7 in (18 mm)
Depth	2.6 in (66 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Weight	0.231 lb(US) (0.105 kg)
color	Dark grey

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0I11
GTIN	3389110345988
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.457 in (3.700 cm)
Package 1 Width	3.268 in (8.300 cm)
Package 1 Length	3.701 in (9.400 cm)
Package weight(Lbs)	3.810 oz (108.000 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

GVAU...



Technical Illustration

Assembly's dimensions

