



### Main

Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	A-L ACPL closing plate

### Complementary

Meter socket rated current	320 A
Number of jaws	4 with jaw release
Bypass type	Lever bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure Material	Steel
Electrical connection	Lugs 0.5" hex
Service feed location	UG
Wiring configuration	3-wire
Device mounting	Surface
AWG gauge	AWG 6...350 kcmil aluminium/copper/line side AWG 6...350 kcmil aluminium/copper/service ground

### Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

### Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901205395
Returnability	No
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.80 in (19.812 cm)
Package 1 Width	17.10 in (43.434 cm)
Package 1 Length	35.80 in (90.932 cm)
Package 1 Weight	39.00 lb(US) (17.69 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------